

# SOMMARIO

Introduzione.....	2
Scopo del documento.....	2
Applicabilità.....	2
Formato degli schemi .....	2
GMBaseMessage.xsd.....	3
GMMessage.xsd .....	4
BaseMessageTypes.xsd .....	5
Types.xsd .....	7
Transazioni xml messe a disposizione degli operatori.....	15
functional acknowledgment.....	15
Functional acknowledgment positivo.....	15
Functional acknowledgment negativo.....	16
MBBN.....	17
MBBN .....	17
MBBN.xsd.....	19
MBMR.....	20
MBMR.xsd .....	20
Offerte .....	21
Sottomissione di un'offerta .....	21
Modifica di un'offerta.....	22
GMOffer.xsd.....	22
Sottomissione dei prezzi di default.....	23

Sottomissione sia del prezzo di vendita che di acquisto .....	23
Sottomissione del solo prezzo di vendita. il prezzo di acquisto viene revocato.....	24
Revoca di entrambi i prezzi.....	24

## INTRODUZIONE

### SCOPO DEL DOCUMENTO

L'Applicazione PB-GAS mette a disposizione per il download e l'upload diverse informazioni mediante files in formato xml; questo documento descrive le transazioni, in termini di formati, utilizzate all'interno di tali files.

### APPLICABILITÀ

Questo documento contiene il file Excel che descrive le transazioni XML di scambio dati supportate dall'Applicazione PB-GAS.

## FORMATO DEGLI SCHEMI

All'interno della di questa Implementation Guide vengono presentati gli XSD distinti per ogni tipo transazione.

Utilizzando opportunamente l'istruzione "include" è possibile ottenere lo schema *GMMessage* (nello schema contenitore *GMBaseMessage*) che richiama gli xsd specifici di ogni transazione coinvolta nell'applicazione.

Di conseguenza gli esempi indicati nei capitoli successivi mostrano l'xsd della singola transazione e un esempio completo di file.

## GMBASEMESSAGE.XSD

```
<?xml version="1.0" encoding="iso-8859-1"?>
<schema xmlns="http://www.w3.org/2001/XMLSchema"
  targetNamespace="urn:XML-GM" xmlns:pd="urn:XML-GM"
  elementFormDefault="qualified">
  <include schemaLocation="BaseMessageTypes.xsd" />
  <element name="Message">
    <complexType>
      <sequence>
        <element ref="pd:tyVersion" minOccurs="0" maxOccurs="1"/>
        <element name="Header" type="pd:tyHeader" minOccurs="1" maxOccurs="1" />
        <choice>
          <element ref="pd:Transaction" minOccurs="1" maxOccurs="unbounded"/>
          <element name="Error" type="pd:tyError" minOccurs="1" maxOccurs="unbounded" />
        </choice>
      </sequence>
      <attribute name="MessageCode" type="int" use="optional" />
      <attribute name="MessageType" type="pd:tyMessageType" use="optional" />
      <attribute name="MessageDate" type="date" use="required" />
      <attribute name="MessageTime" type="time" use="optional" />
      <!-- Response -->
      <attribute name="ResponseReferenceMessageCode" type="int" use="optional" />
      <attribute name="ResponseMessageStatus" type="pd:tyMessageStatus" use="optional" />
    </complexType>
  </element>
  <element name="TransactionDetail" abstract="true" />
  <element name="Transaction">
    <complexType>
      <choice>
        <element ref="pd:TransactionDetail" minOccurs="1" maxOccurs="1" />
      </choice>
      <attribute name="MPN" type="pd:tyExternalReferenceNumber" use="optional" />
      <!-- Response -->
      <attribute name="ResponseTransactionStatus" type="pd:tyTransactionStatus" use="optional" />
      <attribute name="ResponseProcessingTime" type="dateTime" use="optional" />
      <attribute name="ResponseReferenceTransactionCode" type="int" use="optional" />
    </complexType>
  </element>
  <attribute name="ReferenceTransactionCode" type="int" use="optional" />
  <element name="tyVersion" abstract="true" type="string" />
</schema>
```

## GMMESSAGE.XSD

```
<?xml version="1.0" encoding="iso-8859-1"?>
<schema xmlns="http://www.w3.org/2001/XMLSchema"
  targetNamespace="urn:XML-GM"
  xmlns:pd="urn:XML-GM"
  xmlns:NameSpace1="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified">
  <include schemaLocation="Parameters.xsd" />
  <include schemaLocation="GMBaseMessage.xsd" />
  <include schemaLocation="GMMarketPlayer.xsd" />
  <include schemaLocation="FunctionalAcknowledgement.xsd" />
  <include schemaLocation="GMUsers.xsd" />
  <include schemaLocation="GMUserInformations.xsd" />
  <include schemaLocation="GMOffer.xsd" />
  <include schemaLocation="GMSessions.xsd" />
  <include schemaLocation="GMOfferChangeStatus.xsd" />
  <include schemaLocation="GMMarketPlayerInformations.xsd" />
  <include schemaLocation="GMProducts.xsd" />
  <include schemaLocation="BN.xsd" />
  <include schemaLocation="MBBN.xsd" />
  <include schemaLocation="MR.xsd" />
  <include schemaLocation="MBMR.xsd" />
  <include schemaLocation="SessionResult.xsd" />
  <include schemaLocation="MarketPlayerResult.xsd" />
  <include schemaLocation="GMMarketPlayersAccount.xsd" />
  <include schemaLocation="GMAccountActivity.xsd" />
  <include schemaLocation="SNAMPSVItem.xsd" />
  <include schemaLocation="SNAMMarginItem.xsd" />
  <include schemaLocation="GMMarketPlayerMarketInformation.xsd" />
  <include schemaLocation="GMUserMarketInformation.xsd" />
  <include schemaLocation="StorageOperatorEnabling.xsd"></include>
  <include schemaLocation="GMSettlementAction.xsd" />
  <include schemaLocation="DefaultPrices.xsd"></include>
  <include schemaLocation="SNAMWarrantyItem.xsd"></include>

  <element name="Version" substitutionGroup="pd:tyVersion" type="string" />
  <element name="MarketPlayer" substitutionGroup="pd:TransactionDetail" type="pd:MarketPlayers" />
  <element name="MarketPlayerInformation" substitutionGroup="pd:TransactionDetail" type="pd:MarketPlayerInformations" />
  <element name="User" substitutionGroup="pd:TransactionDetail" type="pd:Users" />
  <element name="UserInformation" substitutionGroup="pd:TransactionDetail" type="pd:UserInformations" />
  <element name="UserMarketInformation" substitutionGroup="pd:TransactionDetail" type="pd:UserMarketInformation" />
  <element name="Offer" substitutionGroup="pd:TransactionDetail" type="pd:Offers" />
```

```

<element name="OfferChangeStatus" substitutionGroup="pd:TransactionDetail" type="pd:OffersChangeStatus" />
<element name="Session" substitutionGroup="pd:TransactionDetail" type="pd:Sessions" />
<element name="Product" substitutionGroup="pd:TransactionDetail" type="pd:Products" />
<element name="Parameter" substitutionGroup="pd:TransactionDetail" type="pd:Parameters" />
<element name="FunctionalAcknowledgement" substitutionGroup="pd:TransactionDetail" type="pd:FunctionalAcknowledgements" />
<element name="BN" substitutionGroup="pd:TransactionDetail" type="pd:BNS" />
<element name="MBBN" substitutionGroup="pd:TransactionDetail" type="pd:MBBNs" />
<element name="SessionResult" substitutionGroup="pd:TransactionDetail" type="pd:SessionResults" />
<element name="MarketPlayerResult" substitutionGroup="pd:TransactionDetail" type="pd:MarketPlayerResults" />
<element name="MarketPlayersAccount" substitutionGroup="pd:TransactionDetail" type="pd:MarketPlayerAccounts" />
<element name="MarketPlayerMarketInformation" substitutionGroup="pd:TransactionDetail" type="pd:MarketPlayerMarketInformation" />
<element name="Account_Activity" substitutionGroup="pd:TransactionDetail" type="pd:AccountActivity" />
<element name="SNAM_PSVItem" substitutionGroup="pd:TransactionDetail" type="pd:SNAMPSVItem" />
<element name="SNAM_MarginItem" substitutionGroup="pd:TransactionDetail" type="pd:SNAMMarginItem" />
<element name="MR" substitutionGroup="pd:TransactionDetail" type="pd:MRs" />
<element name="MBMR" substitutionGroup="pd:TransactionDetail" type="pd:MBMRs" />
<element name="StorageOperatorEnabling" substitutionGroup="pd:TransactionDetail" type="pd:StorageOperatorEnabling"></element>
<element name="SettlementAction" substitutionGroup="pd:TransactionDetail" type="pd:SettlementAction"/>
<element name="DefaultPrices" substitutionGroup="pd:TransactionDetail" type="pd:DefaultPrices"></element>
<element name="SNAMWarrantyItem" substitutionGroup="pd:TransactionDetail" type="pd:SNAMWarrantyItem"></element>
</schema>

```

## BASEMESSAGETYPES.XSD

```

<?xml version="1.0" encoding="iso-8859-1" ?>
<schema id="MessageTypes"
  xmlns="http://www.w3.org/2001/XMLSchema"
  targetNamespace="urn:XML-GM"
  xmlns:pd="urn:XML-GM"
  elementFormDefault="qualified">

  <complexType name="tyError">
    <attribute name="Code" type="string" use="required" />
    <attribute name="Description" type="string" use="required" />
  </complexType>

  <complexType name="tyHeader">
    <sequence>
      <element name="Sender" type="pd:tyAddress"/>
      <element name="Receiver" type="pd:tyAddress"/>
    </sequence>
  </complexType>

```

```
<complexType name="tyAddress">
  <sequence>
    <element name="OperatorMsgCode" type="pd:tyOperatorMsgCode"/>
    <element name="CompanyName" type="pd:tyCompanyName" minOccurs="0"/>
    <element name="UserMsgCode" type="pd:tyUserMsgCode" minOccurs="0"/>
  </sequence>
</complexType>

<simpleType name="tyOperatorMsgCode">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="16" />
  </restriction>
</simpleType>

<simpleType name="tyUserMsgCode">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="50" />
  </restriction>
</simpleType>

<simpleType name="tyMessageCode">
  <restriction base="string">
    <minLength value="32" />
    <maxLength value="32" />
  </restriction>
</simpleType>

<simpleType name="tyTransactionCode">
  <restriction base="string">
    <minLength value="32" />
    <maxLength value="32" />
  </restriction>
</simpleType>

<simpleType name="tyTransactionStatus">
  <restriction base="string">
    <enumeration value="Accepted" />
    <enumeration value="Rejected" />
  </restriction>
</simpleType>
```

```

<simpleType name="tyMessageType">
  <restriction base="string">
    <enumeration value="Request" />
    <enumeration value="Response" />
    <enumeration value="Notify" />
  </restriction>
</simpleType>

<simpleType name="tyMessageStatus">
  <restriction base="string">
    <enumeration value="Accepted" />
    <enumeration value="Rejected" />
    <enumeration value="PartiallyAccepted" />
  </restriction>
</simpleType>

<simpleType name="tyCompanyName">
  <restriction base="string">
    <minLength value="1"/>
    <maxLength value="60"/>
  </restriction>
</simpleType>

<simpleType name="tyExternalReferenceNumber">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="32" />
  </restriction>
</simpleType>

</schema>

```

## TYPES.XSD

```

<?xml version="1.0" encoding="iso-8859-1" ?>
<schema id="MessageTypes"
  xmlns="http://www.w3.org/2001/XMLSchema"
  targetNamespace="urn:XML-GM"
  xmlns:pd="urn:XML-GM"
  elementFormDefault="qualified">

  <element name="RejectInformation">

```

```
<complexType>
  <sequence>
    <element name="Reason" type="pd:ty032len"/>
    <element name="ReasonText" type="pd:ty01024len" minOccurs="0" maxOccurs="1"/>
  </sequence>
</complexType>
</element>
```

```
  <simpleType name="ty1len">
    <restriction base="string">
      <minLength value="1" />
      <maxLength value="3" />
    </restriction>
  </simpleType>
```

```
<simpleType name="ty2len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="2" />
  </restriction>
</simpleType>
```

```
<simpleType name="ty3len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="3" />
  </restriction>
</simpleType>
```

```
<simpleType name="ty04len">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="4" />
  </restriction>
</simpleType>
```

```
<simpleType name="ty4len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="4" />
  </restriction>
</simpleType>
```

```
<simpleType name="ty08len">
  <restriction base="string">
```

```
    <minLength value="0" />
    <maxLength value="8" />
  </restriction>
</simpleType>

<simpleType name="ty8len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="8" />
  </restriction>
</simpleType>

<simpleType name="ty016len">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="16" />
  </restriction>
</simpleType>

<simpleType name="ty16len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="16" />
  </restriction>
</simpleType>

<simpleType name="ty032len">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="32" />
  </restriction>
</simpleType>

<simpleType name="ty32len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="32" />
  </restriction>
</simpleType>

<simpleType name="ty30len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="30" />
  </restriction>
</simpleType>
```

```
</simpleType>

<simpleType name="ty50len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="50" />
  </restriction>
</simpleType>

<simpleType name="ty064len">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="64" />
  </restriction>
</simpleType>

<simpleType name="ty64len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="64" />
  </restriction>
</simpleType>

<simpleType name="ty0128len">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="128" />
  </restriction>
</simpleType>

<simpleType name="ty128len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="128" />
  </restriction>
</simpleType>

<simpleType name="ty0256len">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="256" />
  </restriction>
</simpleType>

<simpleType name="ty256len">
```

```
<restriction base="string">
  <minLength value="1" />
  <maxLength value="256" />
</restriction>
</simpleType>
```

```
<simpleType name="ty0512len">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="512" />
  </restriction>
</simpleType>
```

```
<simpleType name="ty512len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="512" />
  </restriction>
</simpleType>
```

```
<simpleType name="ty01024len">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="1024" />
  </restriction>
</simpleType>
```

```
<simpleType name="ty1024len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="1024" />
  </restriction>
</simpleType>
```

```
<simpleType name="ty33len">
  <restriction base="string">
    <minLength value="1" />
    <maxLength value="33" />
  </restriction>
</simpleType>
```

```
<simpleType name="ty050len">
  <restriction base="string">
    <minLength value="0" />
    <maxLength value="50" />
  </restriction>
</simpleType>
```

```

    </restriction>
</simpleType>

<simpleType name="tyDate">
  <restriction base="integer">
    <minInclusive value="19000101"/>
    <maxInclusive value="29001231"/>
  </restriction>
</simpleType>

<simpleType name="tyHourIntervalType">
  <restriction base="integer">
    <minInclusive value="1"/>
    <maxInclusive value="25"/>
  </restriction>
</simpleType>

<simpleType name="tyMarketPlayerType">
  <restriction base="string">
    <enumeration value="OWN"/>
    <enumeration value="REG"/>
    <enumeration value="VEN"/>
    <enumeration value="VENR"/>
    <enumeration value="VENC"/>
    <enumeration value="REGM"/>
    <enumeration value="REGP"/>
    <enumeration value="SNAM"/>
    <enumeration value="STOR"/>
  </restriction>
</simpleType>

<simpleType name="tyResultType">
  <restriction base="string">
    <enumeration value="ZoneResults"/>
    <enumeration value="InterZoneResults"/>
    <enumeration value="GenericMarketResults"/>
  </restriction>
</simpleType>

<simpleType name="tyQtyMWh">
  <restriction base="string">
    <!-- 99999999 ==> senza separatore migliaia solo intero senza decimali senza segno -->
    <!-- 99999999,9999 ==> senza separatore migliaia con al massimo 4 decimali senza segno -->
    <pattern value="^\d{1,12}(\,\d{1,3})|^\d{1,12}(\,\d{1,2})|^\d{1,12}(\,\d{1,1})|^\d{1,12}$"/>
  </restriction>

```

```

</simpleType>

<simpleType name="tyCoefficient">
  <restriction base="string">
    <!-- 99999999 ==> senza separatore migliaia solo intero senza decimali senza segno -->
    <!-- 99999999,9999 ==> senza separatore migliaia con al massimo 4 decimali senza segno -->
    <pattern value="^\d{1,12}(\,\d{1,3})|^?\d{1,12}(\,\d{1,2})|^?\d{1,12}(\,\d{1,1})|^?\d{1,12}$"/>
  </restriction>
</simpleType>

<simpleType name="tyPrice">
  <restriction base="string">
    <!-- 99999999 ==> senza separatore migliaia solo intero senza decimali senza segno -->
    <!-- 99999999,9999 ==> senza separatore migliaia con al massimo 3 decimali senza segno -->
    <pattern value="^\d{1,12}(\,\d{1,4})?$/>
  </restriction>
</simpleType>

<simpleType name="tyPriceTwoDecimals">
  <restriction base="string">
    <!-- 99999999 ==> senza separatore migliaia solo intero senza decimali senza segno -->
    <!-- 99999999,9999 ==> senza separatore migliaia con al massimo 3 decimali senza segno -->
    <pattern value="^\d{1,12}(\,\d{1,2})?$/>
  </restriction>
</simpleType>

<simpleType name="tyQuantity">
  <restriction base="string">
    <!-- 99999999 ==> senza separatore migliaia solo intero senza decimali senza segno -->
    <!-- 99999999,9999 ==> senza separatore migliaia con al massimo 1 decimali senza segno -->
    <pattern value="^\d{1,12}(\,\d{1,1})?$/>
  </restriction>
</simpleType>

<simpleType name="tySignedQuantity">
  <restriction base="string">
    <!-- 99999999 ==> senza separatore migliaia solo intero senza decimali senza segno -->
    <!-- 99999999,9999 ==> senza separatore migliaia con al massimo 1 decimali senza segno -->
    <pattern value="^[+]\d{1,12}(\,\d{1,1})?$/>
  </restriction>
</simpleType>

<simpleType name="tyAwardedPrice">
  <restriction base="string">
    <!-- 99999999 ==> senza separatore migliaia solo intero senza decimali senza segno -->

```

```

    <!-- 99999999,9999 ==> senza separatore migliaia con al massimo 4 decimali senza segno -->
    <pattern value="^\d{1,12}(\,\d{1,6})|^\d{1,12}(\,\d{1,5})|^\d{1,12}(\,\d{1,4})|^\d{1,12}(\,\d{1,3})|^\d{1,12}(\,\d{1,2})|^\d{1,12}(\,\d{1,1})|^\d{1,12}$"/>
  </restriction>
</simpleType>

<simpleType name="tyFlowMwh">
  <restriction base="string">
    <!-- 99.999.999 ==> con separatore migliaia solo intero senza decimali con o senza segno -->
    <!-- 99999999 ==> senza separatore migliaia solo intero senza decimali con o senza segno -->
    <!-- 99.999.999,999 ==> con separatore migliaia con al massimo 3 decimali con o senza segno -->
    <!-- 99999999,999 ==> senza separatore migliaia con al massimo 3 decimali con o senza segno -->
    <pattern value="^[+-]?(\d{1,12}(\,\d{1,3})|^\d{1,12}(\,\d{1,2})|^\d{1,12}(\,\d{1,1})|^\d{1,12}$"/>
  </restriction>
</simpleType>

<simpleType name="tyUnitOfMeasure">
  <restriction base="string">
    <enumeration value="MWh"/>
  </restriction>
</simpleType>

<simpleType name="tyTransactionType">
  <restriction base="string">
    <enumeration value="MarketPlayers" />
    <enumeration value="Users" />
    <enumeration value="UserInformations" />
    <enumeration value="Parameters" />
    <enumeration value="FunctionalAcknowledgement" />
    <enumeration value="Offers" />
    <enumeration value="Sessions" />
    <enumeration value="BidsOffers" />
    <enumeration value="MarketSessions" />
    <enumeration value="MarketResults" />
    <enumeration value="BidNotifications" />
    <enumeration value="BNS" />
    <enumeration value="MBBNS" />
    <enumeration value="MRs" />
    <enumeration value="MBMRs" />
    <enumeration value="SessionResults" />
    <enumeration value="MarketPlayerResults" />
    <enumeration value="MarketPlayerInformations" />
  </restriction>
</simpleType>

```

```

<enumeration value="MarketPlayersAccount" />
<enumeration value="AccountActivity" />
<enumeration value="SNAMPSVItem" />
<enumeration value="SNAMMarginItem" />
<enumeration value="StorageOperatorEnabling"></enumeration>
<enumeration value="DefaultPrices"></enumeration>
<enumeration value="SNAMWarrantyItem"></enumeration>
<enumeration value="Unknown" />
</restriction>
</simpleType>

<simpleType name="tyOperation">
  <restriction base="string">
    <enumeration value="AddNew"/>
    <enumeration value="Modify"/>
  </restriction>
</simpleType>

  <simpleType name="tyOperation2">
    <restriction base="string">
      <enumeration value="AddNew"/>
      <enumeration value="DeleteInsert"/>
    </restriction>
  <enumeration value="Confirm"/>
</simpleType>
</schema>

```

## TRANSAZIONI XML MESSE A DISPOSIZIONE DEGLI OPERATORI

### FUNCTIONAL ACKNOWLEDGMENT

#### *FUNCTIONAL ACKNOWLEDGMENT POSITIVO*

```

<?xml version="1.0" encoding="iso-8859-1"?>
<Message xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema" MessageType="Response"
MessageDate="2010-12-01" MessageTime="09:34:04.3972610+01:00" ResponseMessageStatus="Accepted" xmlns="urn:XML-GM">
  <Header>

```

```

<Sender>
  <OperatorMsgCode>IDGMEGAS</OperatorMsgCode>
</Sender>
<Receiver>
  <OperatorMsgCode>9999999</OperatorMsgCode>
</Receiver>
</Header>
<Transaction>
  <FunctionalAcknowledgement TransactionType="Offers" Status="Accepted" XmlOrder="1" RefId="827" />
</Transaction>
<Transaction>
  <FunctionalAcknowledgement TransactionType="Offers" Status="Accepted" XmlOrder="2" RefId="828" />
</Transaction>
</Message>

```

### *FUNCTIONAL ACKNOWLEDGMENT NEGATIVO*

```

<?xml version="1.0" encoding="iso-8859-1"?>
<Message xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema" MessageType="Response"
MessageDate="2010-12-01" MessageTime="09:28:47.6849168+01:00" ResponseMessageStatus="Rejected" xmlns="urn:XML-GM">
  <Header>
    <Sender>
      <OperatorMsgCode>IDGMEGAS</OperatorMsgCode>
    </Sender>
    <Receiver>
      <OperatorMsgCode>9999999</OperatorMsgCode>
    </Receiver>
  </Header>
  <Transaction>
    <FunctionalAcknowledgement TransactionType="Offers" Status="Rejected" XmlOrder="1">
      <RejectInformation>
        <Reason>OF03</Reason>
        <ReasonText> no open session found</ReasonText>
      </RejectInformation>
    </FunctionalAcknowledgement>
  </Transaction>
</Message>

```

### *FUNCTIONALACKNOWLEDGEMENT.XSD*

```

<?xml version="1.0" encoding="iso-8859-1" ?>
<schema
  xmlns="http://www.w3.org/2001/XMLSchema"
  targetNamespace="urn:XML-GM"

```

```

xmlns:pd="urn:XML-GM"
elementFormDefault="qualified">
<include schemaLocation="BaseMessageTypes.xsd" />
<include schemaLocation="Types.xsd" />
<complexType name="FunctionalAcknowledgements">
  <sequence>
    <element ref = "pd:RejectInformation" minOccurs="0" maxOccurs="unbounded"/>
  </sequence>
  <attribute name="TransactionType" type="pd:tyTransactionType" use="optional"/>
  <attribute name="Status" type="pd:tyTransactionStatus" use="required"/>
  <attribute name="MPN" type="string" use="optional"/>
  <attribute name="XmlOrder" type="int" use="required"/>
  <attribute name="RefId" type="int" use="optional"/>
</complexType>
</schema>

```

## MBBN

### *MBBN*

```

<?xml version="1.0" encoding="iso-8859-1"?>
<Message xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema" MessageType="Notify" MessageDate="2011-09-
07" MessageTime="08:55:13.8351460+02:00" xmlns="urn:XML-GM">
  <Header>
    <Sender>
      <OperatorMsgCode>IDGMEGAS</OperatorMsgCode>
    </Sender>
    <Receiver>
      <OperatorMsgCode>99999999</OperatorMsgCode>
    </Receiver>
  </Header>
  <Transaction>
    <MBBN>
      <Date>2011-09-06</Date>
      <OfferId>590</OfferId>
      <ProductName>MGAS</ProductName>
      <ExecutionDetails>
        <SubmittedPrice>12,00</SubmittedPrice>
      </ExecutionDetails>
    </MBBN>
  </Transaction>
</Message>

```

```
<AwardedPrice>12,00</AwardedPrice>
<Market>MBS</Market>
<SubmittedQty>10,0</SubmittedQty>
<AwardedQty>8,3</AwardedQty>
<Status>Awarded</Status>
<Purpose>A</Purpose>
</ExecutionDetails>
</MBBN>
</Transaction>
<Transaction>
  <MBBN>
    <Date>2011-09-06</Date>
    <OfferId>594</OfferId>
    <ProductName>MGAS</ProductName>
    <ExecutionDetails>
      <SubmittedPrice>12,00</SubmittedPrice>
      <AwardedPrice>12,00</AwardedPrice>
      <Market>MBS</Market>
      <SubmittedQty>10,0</SubmittedQty>
      <AwardedQty>8,3</AwardedQty>
      <RefusedQty>-10,0</RefusedQty>
      <Status>Awarded</Status>
      <Purpose>A</Purpose>
      <MPN>MARGIN VIOLATION GENERATED OFFER</MPN>
    </ExecutionDetails>
  </MBBN>
</Transaction>
<Transaction>
  <MBBN>
    <Date>2011-09-06</Date>
    <OfferId>598</OfferId>
    <ProductName>MGAS</ProductName>
    <ExecutionDetails>
      <SubmittedPrice>12,00</SubmittedPrice>
      <AwardedPrice>12,00</AwardedPrice>
      <Market>MBS</Market>
      <SubmittedQty>30,0</SubmittedQty>
      <AwardedQty>20,3</AwardedQty>
      <RefusedQty>4,0</RefusedQty>
      <Status>Awarded</Status>
      <Purpose>A</Purpose>
      <MPN>MARGIN VIOLATION</MPN>
    </ExecutionDetails>
  </MBBN>
</Transaction>
```

</Message>

## MBBN.XSD

```
<?xml version="1.0" encoding="iso-8859-1"?>
<schema xmlns="http://www.w3.org/2001/XMLSchema"
  targetNamespace="urn:XML-GM" xmlns:pd="urn:XML-GM"
  elementFormDefault="qualified">
  <include schemaLocation="Types.xsd" />
  <complexType name="MBBNs">
    <sequence>
      <element name="Date" type="date" minOccurs="1" maxOccurs="1" />
      <element name="OfferId" type="int" minOccurs="1" maxOccurs="1" />
      <element name="ProductName" type="pd:ty16len" minOccurs="1" maxOccurs="1" />
      <element name="VendorCode" type="pd:ty16len" minOccurs="0" maxOccurs="1" />
      <choice>
        <element name="OffersDetails" type="pd:MBBNDetail" minOccurs="1" maxOccurs="unbounded" />
        <element name="ExecutionDetails" type="pd:MBBNExecutionDetail" minOccurs="1" maxOccurs="unbounded" />
      </choice>
    </sequence>
  </complexType>
  <complexType name="MBBNDetail">
    <sequence>
      <element name="Price" type="pd:tyPrice" minOccurs="1" maxOccurs="1" />
      <element name="Contracts" type="pd:tyQuantity" minOccurs="1" maxOccurs="1" />
    </sequence>
    <attribute name="OfferMatchId" type="int" use="optional" />
  </complexType>
  <complexType name="MBBNExecutionDetail">
    <sequence>
      <element name="SubmittedPrice" type="pd:tyPriceTwoDecimals" minOccurs="1" maxOccurs="1" />
      <element name="AwardedPrice" type="pd:tyPriceTwoDecimals" minOccurs="0" maxOccurs="1" />
      <element name="Market" type="string" minOccurs="0" maxOccurs="1"/>
      <element name="SubmittedQty" type="pd:tyQuantity" minOccurs="1" maxOccurs="1" />
      <element name="AwardedQty" type="pd:tyQuantity" minOccurs="0" maxOccurs="1" />
      <element name="RefusedQty" type="pd:tySignedQuantity" minOccurs="0" maxOccurs="1" />
      <element name="Status" type="string" minOccurs="1" maxOccurs="1" />
      <element name="RejectInfo" type="string" minOccurs="0" maxOccurs="unbounded" />
      <element name="Purpose" type="string" minOccurs="1" maxOccurs="1"/>
      <element name="MPN" type="string" minOccurs="0" maxOccurs="1"/>
    </sequence>
  </complexType>
</schema>
```

## MBMR

```
<?xml version="1.0" encoding="iso-8859-1"?>
<Message xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema" MessageType="Request"
MessageDate="2010-12-01" MessageTime="10:16:48.4291204+01:00" xmlns="urn:XML-GM">
  <Header>
    <Sender>
      <OperatorMsgCode>IDGMEGAS</OperatorMsgCode>
    </Sender>
    <Receiver>
      <OperatorMsgCode>MK* </OperatorMsgCode>
    </Receiver>
  </Header>
  <Transaction>
    <MR>
      <MarginalPrice>32,00</MarginalPrice>
      <MarginalQty>75,5</MarginalQty>
      <SellQty>163,3</SellQty>
      <BuyQty>141,8</BuyQty>
      <FlowDate>2011-11-16</FlowDate>
    </MR>
  </Transaction>
</Message>
```

## MBMR.XSD

```
<?xml version="1.0" encoding="iso-8859-1"?>
<schema xmlns="http://www.w3.org/2001/XMLSchema"
  targetNamespace="urn:XML-GM" xmlns:pd="urn:XML-GM"
  elementFormDefault="qualified">
  <include schemaLocation="Types.xsd" />
  <complexType name="MBMRs">
    <sequence>
      <element name="MarginalPrice" type="pd:tyPriceTwoDecimals" minOccurs="1" maxOccurs="1" />
      <element name="MarginalQty" type="pd:tyQuantity" minOccurs="1" maxOccurs="1" />
      <element name="SellQty" type="pd:tyQuantity" minOccurs="1" maxOccurs="1" />
      <element name="BuyQty" type="pd:tyQuantity" minOccurs="1" maxOccurs="1" />
    </sequence>
  </complexType>
</schema>
```

```
    <element name="FlowDate" type="date" minOccurs="1" maxOccurs="1"></element>
  </sequence>
</complexType>
</schema>
```

## OFFERTE

### SOTTOMISSIONE DI UN'OFFERTA

```
<?xml version="1.0" encoding="iso-8859-1"?>
<Message xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema" MessageType="Request" MessageDate="2011-09-
16" MessageTime="09:07:03.9187565+02:00" xmlns="urn:XML-GM">
  <Header>
    <Sender>
      <OperatorMsgCode>9999999</OperatorMsgCode>
    </Sender>
    <Receiver>
      <OperatorMsgCode>IDGMEGAS</OperatorMsgCode>
    </Receiver>
  </Header>
  <Transaction>
    <Offer OfferType="V">
      <ProductName>MGAS</ProductName>
      <Quantity>44,5</Quantity>
      <MBPrice>12,45</MBPrice>
      <ExpiryTime>9999-12-31</ExpiryTime>
      <MarketCode>MBS</MarketCode>
      <Notes />
      <Replacement>>false</Replacement>
      <FlowDate>2011-09-17</FlowDate>
      <StorageOperatorCode>88888888</StorageOperatorCode>
    </Offer>
  </Transaction>
  <Transaction>
    <Offer OfferType="A">
      <ProductName>MGAS</ProductName>
      <Quantity>14,5</Quantity>
      <MBPrice>10,15</MBPrice>
      <ExpiryTime>9999-12-31</ExpiryTime>
      <MarketCode>MBS</MarketCode>
```

```
<Notes />
<Replacement>true</Replacement>
<FlowDate>2011-09-17</FlowDate>
<StorageOperatorCode>88888888</StorageOperatorCode>
</Offer>
</Transaction>
</Message>
```

## *MODIFICA DI UN'OFFERTA*

```
<?xml version="1.0" encoding="iso-8859-1"?>
<Message xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema" MessageType="Request" MessageDate="2011-09-
16" MessageTime="09:07:03.9187565+02:00" xmlns="urn:XML-GM">
  <Header>
    <Sender>
      <OperatorMsgCode>9999999</OperatorMsgCode>
    </Sender>
    <Receiver>
      <OperatorMsgCode>IDGMEGAS</OperatorMsgCode>
    </Receiver>
  </Header>
  <Transaction>
    <Offer OfferType="A" OffersId="635">
      <ProductName>MGAS</ProductName>
      <Quantity>14,5</Quantity>
      <MBPrice>9,15</MBPrice>
      <ExpiryTime>9999-12-31</ExpiryTime>
      <MarketCode>MBS</MarketCode>
      <Notes />
      <Replacement>false</Replacement>
      <FlowDate>2011-09-17</FlowDate>
      <StorageOperatorCode>88888888</StorageOperatorCode>
    </Offer>
  </Transaction>
</Message>
```

## *GMOFFER.XSD*

```

<?xml version="1.0" encoding="iso-8859-1"?>
<schema xmlns="http://www.w3.org/2001/XMLSchema"
  targetNamespace="urn:XML-GM" xmlns:pd="urn:XML-GM"
  elementFormDefault="qualified">
<include schemaLocation="Types.xsd" />
<complexType name="Offers">
  <sequence>
    <element name="ProductName" type="pd:ty32len" minOccurs="1" maxOccurs="1" />
    <choice>
      <element name="Contracts" type="int" minOccurs="1" maxOccurs="1"/>
      <element name="Quantity" type="pd:tyQuantity" minOccurs="1" maxOccurs="1" />
    </choice>
    <choice>
      <element name="Price" type="pd:tyPrice" minOccurs="0" maxOccurs="1" />
      <element name="MBPrice" type="pd:tyPriceTwoDecimals" minOccurs="0" maxOccurs="1" />
    </choice>
    <element name="ExpiryTime" type="date" minOccurs="1" maxOccurs="1" />
    <element name="Predefined" type="boolean" minOccurs="0" maxOccurs="1" default="false"></element>
    <element name="MarketCode" type="string" minOccurs="0" maxOccurs="1" />
    <element name="Notes" type="string" minOccurs="0" maxOccurs="1" />
    <element name="Replacement" type="boolean" minOccurs="0" maxOccurs="1"/>
    <element name="FlowDate" type="date" minOccurs="0" maxOccurs="1" nillable="true" />
    <element name="StorageOperatorCode" type="pd:ty32len" minOccurs="0" maxOccurs="1" />
  </sequence>
  <attribute name="SessionsId" type="int" use="optional" default="0" />
  <attribute name="OffersId" type="int" use="optional" default="0" />
  <attribute name="VendorCode" type="pd:ty32len" use="optional" />
  <attribute name="OfferType" type="pd:ty4len" use="required" />
</complexType>
</schema>

```

## SOTTOMISSIONE DEI PREZZI DI DEFAULT

### *SOTTOMISSIONE SIA DEL PREZZO DI VENDITA CHE DI ACQUISTO*

```

<?xml version="1.0" encoding="iso-8859-1"?>
<Message xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema" MessageType="Request" MessageDate="2011-09-
16" MessageTime="09:56:19.9514999+02:00" xmlns="urn:XML-GM">
  <Header>
    <Sender>

```

```
<OperatorMsgCode>9999999</OperatorMsgCode>
</Sender>
<Receiver>
  <OperatorMsgCode>IDGMEGAS</OperatorMsgCode>
</Receiver>
</Header>
<Transaction>
  <DefaultPrices>
    <MarketPlayerCode>9999999</MarketPlayerCode>
    <StorageOperatorCode>88888888</StorageOperatorCode>
    <DefaultUpPrice>22,77</DefaultUpPrice>
    <DefaultDownPrice>11,54</DefaultDownPrice>
  </DefaultPrices>
</Transaction>
</Message>
```

### *SOTTOMISSIONE DEL SOLO PREZZO DI VENDITA. IL PREZZO DI ACQUISTO VIENE REVOCATO*


```
<?xml version="1.0" encoding="iso-8859-1"?>
<Message xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema" MessageType="Request" MessageDate="2011-09-
16" MessageTime="09:56:19.9514999+02:00" xmlns="urn:XML-GM">
  <Header>
    <Sender>
      <OperatorMsgCode>9999999</OperatorMsgCode>
    </Sender>
    <Receiver>
      <OperatorMsgCode>IDGME</OperatorMsgCode>
    </Receiver>
  </Header>
  <Transaction>
    <DefaultPrices>
      <MarketPlayerCode>9999999</MarketPlayerCode>
      <StorageOperatorCode>88888888</StorageOperatorCode>
      <DefaultUpPrice>22,77</DefaultUpPrice>
    </DefaultPrices>
  </Transaction>
</Message>
```

### *REVOCA DI ENTRAMBI I PREZZI*


```
<?xml version="1.0" encoding="iso-8859-1"?>
<Message xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema" MessageType="Request" MessageDate="2011-09-
16" MessageTime="09:56:19.9514999+02:00" xmlns="urn:XML-GM">
  <Header>
```

```
<Sender>  
  <OperatorMsgCode>9999999</OperatorMsgCode>  
</Sender>  
<Receiver>  
  <OperatorMsgCode>88888888</OperatorMsgCode>  
</Receiver>  
</Header>  
<Transaction>  
  <DefaultPrices>  
    <MarketPlayerCode>9999999</MarketPlayerCode>  
    <StorageOperatorCode>88888888</StorageOperatorCode>  
  </DefaultPrices>  
</Transaction>  
</Message>
```


**Caso 1: Sottomissione offerta**



**Caso 2: Sottomissione dei prezzi di default**



**Caso 3: Sottomissione offerta, Chiusura ed esecuzione Mercato**



# Offer Implementation Guide for PB-GAS

Element / Attribute names	Attribute / Element	Valid Information in Field (enumeration)	Data Type	Occurrences Min/Max	Field Length	Definition
<b>Message</b>						
		A/N	A/N	1 for file		
xmlns:xsi	A					Defines the schema instance being used.
xmlns:xsd	A					Associates the actual schema instance being used to the name space.
xmlns	A					
MessageType	A	Request		0/1		Message type
MessageDate	A	Valid date	YYYY-MM-DD	1/1		Date of the message
MessageTime	A			0/1		Time of the message
Header	E	(see Header data structure)		1/1		Contains the sender and the recipient of the message
Transaction	E	(see Transaction data structure)		1 or more		Transaction Container
<b>Header</b>						
Sender	E	(see Sender data structure)		1/1		message sender
Receiver	E	(see Receiver data structure)		1/1		message receiver
<b>Sender</b>						
OperatorMsgCode	E		A/N	1/1	max=16	The unique identifier of the Sender
CompanyName	E		A/N	0/1	max=60	The Name of the Sender
UserMsgCode	E		A/N	0/1	max=50	The unique identifier for the user who sends
<b>Receiver</b>						
OperatorMsgCode	E	IDGMEGAS	A/N	1/1	max=16	The unique identifier of the Receiver
CompanyName	E		A/N	0/1	max=60	The Name of the Receiver
UserMsgCode	E		A/N	0/1	max=50	The unique identifier for the user who receives
<b>Transaction</b>						
MPN	A		A/N	0/1	max=32	External reference number
Offer	E	(see Offer data structure)		1/1		
<b>Offer</b>						
VendorCode	A	PSV code		0/1	max =32	The code of the vendor operator
OfferType	A	V,A		1/1	max =4	The type of the offer: sell (V) or buy (A)
ProductName	E	MGAS	A/N	1/1	max=32	The name of the product associated to the market
Quantity	E	Valid decimal number	999999999999,9	1/1		The quantity
MBPrice	E	Valid decimal number	999999999999,99	1/1		The price
ExpiryTime	E	9999-12-31	YYYY-MM-DD	1/1		Currently unused
Predefined	E	false,true	boolean	0/1		not used
MarketCode	E	MBS	A/N	1/1		The market code the offer is referring to.
Notes	E		A/N	0/1		An operator's note.
Replacement	E	false,true	boolean	1/1		sets if an offer replaces the first submitted offer
StorageOperatorCode	E	PSV code		1/1	max =32	The PSV code of the storage operator.
FlowDate	E	Valid date	YYYY-MM-DD	1/1		The flow date of the session to which the offer is referring.

# Offer Change Implementation Guide for PB-GAS

Element / Attribute names	Attribute / Element	Valid Information in Field (enumeration)	Data Type	Occurrences Min/Max	Field Length	Definition
<b>Message</b>						
		A/N	A/N	1 for file		
xmlns:xsi	A					Defines the schema instance being used.
xmlns:xsd	A					Associates the actual schema instance being used to the name space.
xmlns	A					
MessageType	A	Request		0/1		Message type
MessageDate	A	Valid date	YYYY-MM-DD	1/1		Date of the message
MessageTime	A			0/1		Time of the message
Header	E	(see Header data structure)		1/1		Contains the sender and the recipient of the message
Transaction	E	(see Transaction data structure)		1 or more		Transaction Container
<b>Header</b>						
Sender	E	(see Sender data structure)		1/1		message sender
Receiver	E	(see Receiver data structure)		1/1		message receiver
<b>Sender</b>						
OperatorMsgCode	E		A/N	1/1	max=16	The unique identifier of the Sender
CompanyName	E		A/N	0/1	max=60	The Name of the Sender
UserMsgCode	E		A/N	0/1	max=50	The unique identifier for the user who sends
<b>Receiver</b>						
OperatorMsgCode	E	IDGMEGAS	A/N	1/1	max=16	The unique identifier of the Receiver
CompanyName	E		A/N	0/1	max=60	The Name of the Receiver
UserMsgCode	E		A/N	0/1	max=50	The unique identifier for the user who receives
<b>Transaction</b>						
MPN	A		A/N	0/1	max=32	External reference number
Offer	E	(see Offer data structure)		1/1		
<b>Offer</b>						
OffersId	A		integer	1/1		The id of the offer
VendorCode	A	PSV code		1/1	max =32	The code of the vendor operator
OfferType	A	V,A		1/1	max =4	The type of the offer: sell (V) or buy (A)
ProductName	E	MGAS	A/N	1/1	max=32	The name of the product associated to the market
Quantity	E	Valid decimal number	99999999999,9	1/1		The quantity
MBPrice	E	Valid decimal number	99999999999,99	1/1		The price
ExpiryTime	E	9999-12-31	YYYY-MM-DD	1/1		Currently unused
Predefined	E	false,true	boolean	0/1		not used
MarketCode	E	MBS	A/N	1/1		The market code the offer is referring to.
Notes	E		A/N	0/1		An operator's note.
Replacement	E	false,true	boolean	1/1		sets if an offer replaces the first submitted offer
StorageOperatorCode	E	PSV code		1/1	max =32	The PSV code of the storage operator.
FlowDate	E	Valid date	YYYY-MM-DD	1/1		The flow date of the session to which the offer is referring.

# Default Prices Implementation Guide for PB-GAS

Element / Attribute names	Attribute / Element	Valid Information in Field (enumeration)	Data Type	Occurrences Min/Max	Field Length	Definition
<b>Message</b>						
		A/N	A/N	1 for file		
xmlns:xsi	A					Defines the schema instance being used.
xmlns:xsd	A					Associates the actual schema instance being used to the name space.
xmlns	A					
MessageType	A	Request		0/1		Message type
MessageDate	A	Valid date	YYYY-MM-DD	1/1		Date of the message
MessageTime	A			0/1		Time of the message
Header	E	(see Header data structure)		1/1		Contains the sender and the recipient of the message
Transaction	E	(see Transaction data structure)		1 or more		Transaction Container
<b>Header</b>						
Sender	E	(see Sender data structure)		1/1		message sender
Receiver	E	(see Receiver data structure)		1/1		message receiver
<b>Sender</b>						
OperatorMsgCode	E		A/N	1/1	max=16	The unique identifier of the Sender
CompanyName	E		A/N	0/1	max=60	The Name of the Sender
UserMsgCode	E		A/N	0/1	max=50	The unique identifier for the user who sends
<b>Receiver</b>						
OperatorMsgCode	E	IDGMEGAS	A/N	1/1	max=16	The unique identifier of the Receiver
CompanyName	E		A/N	0/1	max=60	The Name of the Receiver
UserMsgCode	E		A/N	0/1	max=50	The unique identifier for the user who receives
<b>Transaction</b>						
MPN	A		A/N	0/1	max=32	External reference number
DefaultPrices	E	(see DefaultPrices data structure)		1/1		
<b>DefaultPrices</b>						
MarketPlayerCode	A	PSV code		1/1	max =32	The code of the operator
StorageOperatorCode	E	PSV code		1/1	max =32	The PSV code of the storage operator.
DefaultUpPrice	E	Valid decimal number	99999999999,99	0/1		The default price for sell offers. If it is not specified (the element does not appear) the previous default price will be deleted.
DefaultDownPrice	E	Valid decimal number	99999999999,99	0/1		The default price for buy offers. If it is not specified (the element does not appear) the previous default price will be deleted.

# Functional Acknowledgment Implementation Guide for PB-GAS

Element / Attribute names	Attribute / Element	Valid Information in Field (enumeration)	Data Type	Occurrences Min/Max	Field Length	Definition
<b>Message</b>						
		A/N	A/N	1 for file		
xmlns:xsi	A					Defines the schema instance being used.
xmlns:xsd	A					Associates the actual schema instance being used to the name space.
xmlns	A					
MessageType	A	Request		0/1		Message type
MessageDate	A	Valid date	YYYY-MM-DD	1/1		Date of the message
MessageTime	A			0/1		Time of the message
Header	E	(see Header data structure)		1/1		Contains the sender and the recipient of the message
Transaction	E	(see Transaction data structure)		1 or more		Transaction Container
<b>Header</b>						
Sender	E	(see Sender data structure)		1/1		message sender
Receiver	E	(see Receiver data structure)		1/1		message receiver
<b>Sender</b>						
OperatorMsgCode	E	IDGMEGAS	A/N	1/1	max=16	The unique identifier of the Sender
CompanyName	E		A/N	0/1	max=60	The Name of the Sender
UserMsgCode	E		A/N	0/1	max=50	The unique identifier for the user who sends
<b>Receiver</b>						
OperatorMsgCode	E		A/N	1/1	max=16	The unique identifier of the Receiver
CompanyName	E		A/N	0/1	max=60	The Name of the Receiver
UserMsgCode	E		A/N	0/1	max=50	The unique identifier for the user who receives
<b>Transaction</b>						
MPN	A		A/N	0/1	max=32	External reference number
FunctionalAcknowledgement	E	(see FunctionalAcknowledgement data structure)		1/1		
<b>FunctionalAcknowledgement</b>						
TransactionType	A		A/N	0/1		The type of transaction the FA is referring to.
Status	A	Accepted, Rejected	A/N	1/1		The outcome of the transaction
MPN	A		A/N	0/1		External reference number
RefId	A		integer	0/1		The id of the submitted offer
XmlOrder	A		integer	1/1		The xml order
RejectInformation	E	(see RejectInformation data structure)		1 or more		
<b>RejectInformation</b>						
Reason	E		A/N	1/1	max=32	The short description of the rejection
ReasonText	E		A/N	0/1	max=1024	The extended description of the rejection

# Market Result Implementation Guide for PB-GAS

Element / Attribute names	Attribute / Element	Valid Information in Field (enumeration)	Data Type	Occurrences Min/Max	Field Length	Definition
<b>Message</b>						
xmlns:xsi	A	A/N	A/N	1 for file		Defines the schema instance being used.
xmlns:xsd	A					Associates the actual schema instance being used to the name space.
xmlns	A					
MessageType	A	Request		0/1		Message type
MessageDate	A	Valid date	YYYY-MM-DD	1/1		Date of the message
MessageTime	A			0/1		Time of the message
Header	E	(see Header data structure)		1/1		Contains the sender and the recipient of the message
Transaction	E	(see Transaction data structure)		1 or more		Transaction Container
<b>Header</b>						
Sender	E	(see Sender data structure)		1/1		message sender
Receiver	E	(see Receiver data structure)		1/1		message receiver
<b>Sender</b>						
OperatorMsgCode	E	IDGMEGAS	A/N	1/1	max=16	The unique identifier of the Sender
CompanyName	E		A/N	0/1	max=60	The Name of the Sender
UserMsgCode	E		A/N	0/1	max=50	The unique identifier for the user who sends
<b>Receiver</b>						
OperatorMsgCode	E		A/N	1/1	max=16	The unique identifier of the Receiver
CompanyName	E		A/N	0/1	max=60	The Name of the Receiver
UserMsgCode	E		A/N	0/1	max=50	The unique identifier for the user who receives
<b>Transaction</b>						
MPN	A		A/N	0/1	max=32	External reference number
MBMR	E	(see MBMRs data structure)		1/1		
<b>MBMRs</b>						
MarginalPrice	E	Valid decimal number	999999999999,99	1/1		Marginal Price
MarginalQty	E	Valid decimal number	999999999999,9	1/1		Marginal Quantity
SellQty	E	Valid decimal number	999999999999,9	1/1		Sell quantity elaborated
BuyQty	E	Valid decimal number	999999999999,9	1/1		Buy quantity elaborated
FlowDate	E	Valid date	YYYY-MM-DD	1/1		The flow date of the market session

# Bid Notification Implementation Guide for PB-GAS

Element / Attribute names	Attribute / Element	Valid Information in Field (enumeration)	Data Type	Occurrences Min/Max	Field Length	Definition
<b>Message</b>						
xmlns:xsi	A	A/N	A/N	1 for file		Defines the schema instance being used.
xmlns:xsd	A					Associates the actual schema instance being used to the name space.
xmlns	A					
MessageType	A	Request		0/1		Message type
MessageDate	A	Valid date	YYYY-MM-DD	1/1		Date of the message
MessageTime	A			0/1		Time of the message
Header	E	(see Header data structure)		1/1		Contains the sender and the recipient of the message
Transaction	E	(see Transaction data structure)		1 or more		Transaction Container
<b>Header</b>						
Sender	E	(see Sender data structure)		1/1		message sender
Receiver	E	(see Receiver data structure)		1/1		message receiver
<b>Sender</b>						
OperatorMsgCode	E	IDGMEGAS	A/N	1/1	max=16	The unique identifier of the Sender
CompanyName	E		A/N	0/1	max=60	The Name of the Sender
UserMsgCode	E		A/N	0/1	max=50	The unique identifier for the user who sends
<b>Receiver</b>						
OperatorMsgCode	E		A/N	1/1	max=16	The unique identifier of the Receiver
CompanyName	E		A/N	0/1	max=60	The Name of the Receiver
UserMsgCode	E		A/N	0/1	max=50	The unique identifier for the user who receives
<b>Transaction</b>						
MPN	A		A/N	0/1	max=32	External reference number
MBBN	E	(see MBBNs data structure)		1/1		
<b>MBBNs</b>						
Date	E		Date	1/1		Flow Date
OfferId	E		integer	1/1		The Offer ID
ProductName	E		A/N	1/1	max=16	The name of product
VendorCode	E		A/N	0/1	max=16	Vendor Code Identifier
ExecutionDetails	E	(see MBBNExecutionDetail data structure)				
<b>MBBNExecutionDetail</b>						
SubmittedPrice	E	Valid decimal number	99999999999,99	1/1		The original offer price
AwardedPrice	E	Valid decimal number	99999999999,99	0/1		The awarded offer price
Market	E	MBS	A/N	0/1		The market Identifier
SubmittedQty	E	Valid decimal number	99999999999,9	1/1		The initial offer quantity
AwardedQty	E	Valid decimal number	99999999999,9	0/1		The awarded quantity
RefusedQty	E	Valid decimal number	99999999999,9	0/1		The refused quantity
Status	E	V, I, D	A/N	1/1		The status of offer
RejectInfo	E		A/N	0 or more		The reasons of the rejection
Purpose	E	A, V	A/N	1/1		Specify if the offer is sell (V) or buy (A)
MPN	E		A/N	0/1		The MPN code inserted in the offers submission